

This Page Is Inserted by IFW Operations
and is not a part of the Official Record

BEST AVAILABLE IMAGES

Defective images within this document are accurate representations of the original documents submitted by the applicant.

Defects in the images may include (but are not limited to):

- BLACK BORDERS
- TEXT CUT OFF AT TOP, BOTTOM OR SIDES
- FADED TEXT
- ILLEGIBLE TEXT
- SKEWED/SLANTED IMAGES
- COLORED PHOTOS
- BLACK OR VERY BLACK AND WHITE DARK PHOTOS
- GRAY SCALE DOCUMENTS

IMAGES ARE BEST AVAILABLE COPY.

**As rescanning documents *will not* correct images,
please do not report the images to the
Image Problem Mailbox.**




INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(51) International Patent Classification ⁶ : G06K 15/00		A1	(11) International Publication Number: WO 00/25260
			(43) International Publication Date: 4 May 2000 (04.05.00)
(21) International Application Number: PCT/US99/24895		(81) Designated States: AE, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BY, CA, CH, CN, CU, CZ, DE, DK, EE, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MD, MG, MK, MN, MW, MX, NO, NZ, PL, PT, RO, RU, SD, SE, SG, SI, SK, SL, TJ, TM, TR, TT, UA, UG, UZ, VN, YU, ZA, ZW, ARIPO patent (GH, GM, KE, LS, MW, SD, SL, SZ, TZ, UG, ZW), Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European patent (AT, BE, CH, CY, DE, DK, ES, FI, FR, GB, GR, IE, IT, LU, MC, NL, PT, SE), OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, GW, ML, MR, NE, SN, TD, TG).	
(22) International Filing Date: 21 October 1999 (21.10.99)		Published With international search report.	
(30) Priority Data: 60/105,508 23 October 1998 (23.10.98) US			
(71) Applicant: COINSTAR, INC. [US/US]; 1800 114th Avenue S.E., Bellevue, WA 98004 (US).			
(72) Inventors: GEIGER, Steven, M.; 6013 228th N.W., Stanwood, WA 98292 (US). BROWN, David, J.; 23333 S.E. 31st Street Court, Issaquah, WA 98027 (US). MANION, Timothy, J.; 4712 46th Avenue S.W., Seattle, WA 98116 (US). SCHERER, Scott, J.; 6139 West Colgate Avenue, Los Angeles, CA 90036 (US).			
(74) Agents: HUGHES, Richard, L. et al.; Sheridan Ross P.C., Suite 1200, 1560 Broadway, Denver, CO 80202-5141 (US).			

(54) Title: COIN-DISCRIMINATOR VOUCHER ANTI-COUNTERFEITING METHOD AND APPARATUS

(57) Abstract

Anti-counterfeiting and counterfeit detection devices and procedures are provided particularly usable in connection with vouchers (5) issued by coin discriminator or coin counting machines. Paper stock (226) may be preprinted with inks which are not readily photocopied without apparent alteration. Preprinting is preferably in two or more orientations such as longitudinal and lateral and preferably some reprinting is positioned closer to the paper stock edge than can typically be achieved using ordinarily available laser printers or inkjet printers (18). A pattern of perforations, preferably micro perforations, are provided in a curved, preferably tightly radiused shape or configuration. Serial numbers (512c) or other identifiers may be reprinted on portions of the paper stock and matching or correlatable numbers printed on such preprinted paper stock substantially at the time of printing the voucher value. Patterns or indicia printed on one surface of the paper are preferably registered with respect to patterns or indicia printed on the opposite side such that a voucher may be validated by verifying proper registration such as when holding a voucher up to a light.



FOR THE PURPOSES OF INFORMATION ONLY

Codes used to identify States party to the PCT on the front pages of pamphlets publishing international applications under the PCT.

AL	Albania	ES	Spain	LS	Lesotho	SI	Slovenia
AM	Armenia	FI	Finland	LT	Lithuania	SK	Slovakia
AT	Austria	FR	France	LU	Luxembourg	SN	Senegal
AU	Australia	GA	Gabon	LV	Latvia	SZ	Swaziland
AZ	Azerbaijan	GB	United Kingdom	MC	Monaco	TD	Chad
BA	Bosnia and Herzegovina	GE	Georgia	MD	Republic of Moldova	TG	Togo
BB	Barbados	GH	Ghana	MG	Madagascar	TJ	Tajikistan
BE	Belgium	GN	Guinea	MK	The former Yugoslav Republic of Macedonia	TM	Turkmenistan
BF	Burkina Faso	GR	Greece	ML	Mali	TR	Turkey
BG	Bulgaria	HU	Hungary	MN	Mongolia	TT	Trinidad and Tobago
BJ	Benin	IE	Ireland	MR	Mauritania	UA	Ukraine
BR	Brazil	IL	Israel	MW	Malawi	UG	Uganda
BY	Belarus	IS	Iceland	MX	Mexico	US	United States of America
CA	Canada	IT	Italy	NE	Niger	UZ	Uzbekistan
CF	Central African Republic	JP	Japan	NL	Netherlands	VN	Viet Nam
CG	Congo	KE	Kenya	NO	Norway	YU	Yugoslavia
CH	Switzerland	KG	Kyrgyzstan	NZ	New Zealand	ZW	Zimbabwe
CI	Côte d'Ivoire	KP	Democratic People's Republic of Korea	PL	Poland		
CM	Cameroon	KR	Republic of Korea	PT	Portugal		
CN	China	KZ	Kazakhstan	RO	Romania		
CU	Cuba	LC	Saint Lucia	RU	Russian Federation		
CZ	Czech Republic	LJ	Liechtenstein	SD	Sudan		
DE	Germany	LK	Sri Lanka	SE	Sweden		
DK	Denmark	LR	Liberia	SG	Singapore		
EE	Estonia						

COIN-DISCRIMINATOR VOUCHER ANTI-COUNTERFEITING METHOD AND APPARATUS

5 The present invention relates to the provision of vouchers in connection with a coin-discriminator and/or counter and in particular ways of deterring, reducing, eliminating or detecting unauthorized duplication or counterfeiting of vouchers.

BACKGROUND INFORMATION

10 At least some types of coin- discriminators are configured to receive a plurality of coins of various denominations, e.g. from untrained users (such as grocery store or other retail location customers), typically including non-coin items and/or foreign or other undesired coins, to discriminate the various denominations of the desired coins (possibly after separating non-coin items and/or undesired coins) to determine the value of the discriminated desired coins, and to output an indication of the value of the total amount
15 of the discriminated, desired coins. Although many forms of such value output may be termed a voucher, including paperless output (such as depositing a value in a user's bank account, e.g. after reading a user's bank card or other identifier), the present invention is particularly directed to devices which include apparatus or procedures for outputting a physical voucher such as a paper voucher with indicia indicating a value related to the
20 total amount of discriminated, desired coins. Although such physical vouchers will be discussed as "paper" voucher hereinbelow, its possible to provide physical vouchers in other forms such as with indicia placed on other substrates such as plastic, cardboard, magnetic or other non-visible information-bearing media and the like.

25 Because a physical or "paper" voucher has value, in the sense that it can be redeemed for, e.g. cash or credit, it is important for the redeemer to have confidence that a voucher which is presented for redemption is genuine, i.e. is not an unauthorized duplicate or counterfeit voucher. Verifying the genuineness of a voucher is especially difficult in the face of sophisticated image production, reproduction or manipulation technologies such as color photocopy technology, color scanning technologies, computer-
30 based printing technologies such as inkjet (including color inkjet) or laser (including color laser) printer, e.g. coupled to personal computers, work stations and the like. Accordingly, it would be useful to provide vouchers whose genuineness can be readily determined, as compared to an unauthorized duplicate or counterfeit voucher, e.g.

produced using such image duplication production, reproduction or manipulation technologies.

5 Some approaches to detecting unauthorized duplication or counterfeiting have involved encrypting certain information which is then printed on the voucher as part of the voucher printing procedure such that decryption provides a level of confidence that the voucher is genuine. One such procedure is described in U.S. Patent Application 09/178,441 (attorney file 3730-908), incorporated herein by reference. Although such encryption/decryption procedures can be quite useful (and, indeed, can, if desired, be used in combination with some or all features of the present invention), there are circumstances in which it may be desirable to provide for other counterfeit detection measures, in 10 addition to or in place of such encryption/decryption measures.

In some circumstances, it may be desirable to provide anti-counterfeit measures or devices which are independent of the need for substantial modification of printing, check-out or verification software (of the type that might be used in connection with encryption/decryption). For example, it may be desired to avoid making modifications to 15 printing software and/or to avoid modifying or providing software for decryption. Furthermore, in some circumstances it may be desired to avoid the personnel training or hardware involved in a decryption verification process. For example, in some circumstances it is desirable to permit the voucher redemption (which may typically occur at a grocery store or other retail location check-out stand) to be performed, in whole or 20 in part, based on a visual inspection of the voucher (e.g. without the need to perform a decryption step). In some circumstances it may be desirable to provide for duplicate/counterfeit detection without the need for using a computer or other equipment.

Many self-service coin-discriminators of a type with which the present invention may be used employ a thermal printer for outputting a paper voucher. Thermal printers 25 can be particularly useful because of the lack of a requirement to replenish ink or toner. Thermal printers typically operate in conjunction with a type of paper specific to thermal printing ("thermal paper"). Thermal paper often has characteristics which limit how the paper may be treated (e.g. limiting the types of ink or other materials that may be used in connection with providing, for example background preprinting, watermarks and the like). 30 Accordingly, it would be useful to provide voucher duplication/counterfeiting detection

or prevention which can be reasonably and feasibly used with thermal papers and/or thermal printers (e.g. without incurring relatively high costs).

Although there are benefits to an anti-counterfeiting system which provides for detection of unauthorized duplications or counterfeits (at least in part) using a visual inspection of the voucher, a system in which all anti-counterfeiting features are features which are normally visible also means that potential counterfeiters can determine what features need to be copied or duplicated by performing a visual inspection of a valid voucher. Accordingly, it would be useful, in some embodiments, to provide at least some anti-counterfeiting features which are not normally visible, i.e. which are not visible in ordinary ambient light of a redemption location.

Because, in at least some systems, voucher redemption is performed at a retail location, such as during ordinary retail purchase "check out", it would be useful to provide anti-counterfeiting procedures or devices which can be performed relatively rapidly so as to avoid checkout line delays. For example, it would be useful if some or all anti-counterfeiting features can be used for verification without the need for special positioning or manipulation of a voucher and/or without the need for manually inputting features or information from the voucher and preferably without the need to provide special equipment for voucher verification at checkout locations.

In situations where coin-discriminators are already being used, it would be useful to provide for voucher anti-counterfeiting measures which include features that can be provided with little or no modification of coin-discriminator hardware and/or retail location check-out hardware. In some embodiments, it would be useful to provide at least some anti-counterfeiting features which can be implemented by loading paper into already-existing coin-discriminators and substantially without modification of coin-discriminator hardware.

SUMMARY OF THE INVENTION

The present invention includes at least one and preferably a plurality of features provided in or on paper (or other substrate) used for printing a voucher. In one embodiment, at least some portions of the paper are pre-printed or otherwise pre-provided (i.e. printed or provided prior to the printing or providing of indicia indicating the value

of the voucher) in ink which is not readily reproducible by ordinary color photocopiers, such as certain fluorescent inks. In one embodiment, the paper (or other substrate) is provided with a plurality of perforations in a pattern which is not readily reproducible such as a pattern including curved or otherwise non-linear patterns of perforation preferably with the perforations being relatively small and closely spaced and the pattern defining relatively tight-radiused but preferably substantially continuous curves.

In one embodiment, the voucher is provided with printing on both surfaces which are registered relative to one another in such a fashion that the registration may be readily verified (e.g. by holding the voucher up to a light or otherwise backlighting a voucher so as to view at least some portions of printing on the two surfaces simultaneously). In some embodiments, portions of the voucher are printed with a material which has relatively low visibility, or is substantially invisible, until such portion is treated or manipulated, e.g. such as by rubbing or scratching with a coin or other object.

Preferably at least two or more anti-counterfeiting features of a voucher can be verified by viewing only one surface of the voucher, i.e. without the need to flip the voucher over to view the opposite side.

In some embodiments, some or all features are features which permit voucher verification using only visual inspection of the voucher, i.e. without the need to use any equipment. In other embodiments, at least one feature is a feature which is not readily apparent in ordinary or typical light (so as to render it difficult for a potential counterfeiter to even be aware of, much less to duplicate, such feature) such as providing markings which fluoresce or otherwise have detectable properties when viewed in specific types of light such as ultraviolet light.

In some embodiments, the voucher paper is preprinted or preprovided with indicia which are oriented in different fashions (such as both vertically and horizontally) and/or are positioned near the edge of the paper or are otherwise oriented or positioned in a fashion which may be difficult to duplicate with typical computer-based printers.

BRIEF DESCRIPTION OF THE DRAWINGS

Fig. 1 is a perspective view of a coin-discriminating device, in an opened configuration, of a type which may be used in at least one implementation of the present invention;

5 Fig. 2 is a block diagram depicting certain components of a coin discriminator of a type which can be used in accordance with implementation of the present invention;

Fig. 3A is a front view of a voucher of a type which may be used according to one embodiment of the present invention;

10 Fig. 3B is a view of the back surface of the voucher of Fig. 3A with Fig. 3B being positioned in alignment with Fig. 3A to show relative locations of features on opposite surfaces;

Fig. 4 is a partial perspective view of a perforation wheel according to an embodiment of the present invention; and

15 Fig. 5 is a front view of a voucher according to one embodiment of the present invention.

DETAILED DESCRIPTION OF THE PREFERRED EMBODIMENT

Fig. 1 is a perspective view of a coin-discriminator of a type which can be used in connection with embodiments of the present invention. The embodiment depicted in Fig 20 1 generally includes a coin counting/sorting portion 12, a voucher dispensing portion 14a and a coupon dispensing portion 14b. In the depicted embodiment, the coin counting portion 12 includes an input tray 16, a coin return region 22, and customer I/O devices, including a keyboard 24, additional keys 26, a speaker 28 and a video screen 32. The apparatus can include various indicia, signs, displays, advertisement and the like on its 25 external surfaces. A power cord 34 provides power to the mechanism.

Preferably, when the doors 36a, 36b are in the open position as shown, most or all of the components are accessible for cleaning and/or maintenance. In the depicted embodiment, a voucher printer 18 is mounted on the inside of the door 36a. A number of printers can be used for this purpose. In one embodiment, a model KLDS0503 printer, 30 available from Axiohm is used. The right-hand portion of the cabinet includes a coupon feeder 42 for dispensing, e.g., pre-printed manufacturer coupon sheets through a chute

44 to a coupon hopper on the outside portion of the door 36b. A computer 46, in the depicted embodiment, is positioned at the top of the right hand portion of the cabinet in order to provide a relatively clean, location for the computer. An I/O board 48 is positioned adjacent the sheet feeder 42.

5 The general coin path for the embodiment depicted in Fig 1 is from the input tray 16, down first and second chutes to a trommel 52, to a coin pickup assembly 54, along a coin rail 56 and past a sensor 58. If, based on sensor data, it is determined that the coin can and should be accepted, a controllable deflector door 62 is activated to divert coins from their gravitational path to coin tubes 64a, b for delivery to coin trolleys 66a, b. If
10 it has not been determined that a coin can and should be accepted, the door 62 is not activated and coins (or other objects) continue down their gravitational or default path to a reject chute 68 for delivery to a customer-accessible reject or return box 22.

 In use, a user is provided with instructions such as on computer screen 32. The user places a mass of coins, typically of a plurality of denominations (typically
15 accompanied by dirt or other non-coin objects) in the input tray 16. The user is prompted to push a button to inform the machine that the user wishes to have coins discriminated. Thereupon, the computer causes an input gate (not shown) to open and provides a signal to prompt the user to begin feeding coins. When the gate is open, a motor is activated to begin rotating the trommel assembly 52. The user moves coins over the peaked output
20 edge 72 of the input tray 16, typically by lifting or pivoting the tray by handle 74, and/or manually feeding coins over the peak 72. The coins pass the gate (typically set to prevent passage of more than a predetermined number of stacked coins, such as by defining an opening equal to about 3.5 times a typical coin thickness). Instructions on the screen 32 may be used to tell the user to continue or discontinue feeding coins, can relay the status
25 of the machine, the amount counted thus far, provide encouragement or advertising messages and the like. The coin rail 56 functions to receive coins output by the coin pickup assembly 54, and transports the coins in a singulated (one-at-a-time) fashion past the sensor 58 to the diverting door 62. Once no more coins are detected and/or in response to user input, the system determines that the transaction is complete and the
30 computer 46 will send instructions to the printer 18 causing the printer to output a voucher of a type which may be exchanged for goods, services or cash.

Fig. 2 is a block diagram of a coin-discriminator of a type which can be used in accordance with implementations of the present invention. Some of the items in Fig. 2 correspond to components in the device of Fig. 1. In operation, an untrained user, such as a grocery store or other retail location customer places a plurality of coins of unknown value and random orientation in a receiving tray or other receiving area 16. Typically, foreign or other undesirable coins and foreign objects such as currency or other paper, paper clips, lint, keys and the like are mixed with the desired coins and placed, such as being poured or dumped, substantially all at once, into the tray 16. A conveyance device 214, such as a chute, trough, slide or the like, or including positive drive or otherwise moving conveyances such as conveyer belts, Archimedes' screws and the like, are used to provide at least some of the desired coins from the receiving area 16 to a coin-discriminator 218. Preferably, prior to entry to the discriminator 218, at least some of the foreign objects or materials are separated such as using airflow, vacuum, gravitational separation, size-based separation (such as through openings of predetermined size or sizes) and the like. The discriminator 216 provides a signal to a calculating device, preferably a computer with sufficient information regarding the number of desired coins of various denominations such that the computer 46 can output or store a value equal to or related to (such as being a predetermined amount or portion less than) the value of the desired discriminated coins which are then placed in one or more bins 66 or other receiving regions. The computer 46, at the end of a transaction (as indicated by lack of further input of coins for a predetermined period and/or input from a user) controls a paper voucher printer 18 to print, on paper (or other substrates) obtained from a roll of paper or other paper supply 226 a redeemable voucher for an amount related to the total value of the discriminated desired coins for this transaction.

Figs. 3A and 3B depict a number of features of a voucher useful for avoiding, preventing and/or detecting unauthorized duplication or counterfeiting of vouchers. Figs. 3A and 3B are presented herein in a fashion which indicates the relative positions of the indicia or marking on the front surface (Fig 3A) and the opposite or rear surface (Fig. 3B). I.e., features which are shown as aligned in corresponding locations in Figs. 3A and 3B are features which would appear at corresponding longitudinal positions on opposite surfaces of the voucher.

In the depicted embodiment, the rear surface (Fig. 3B) of the voucher includes printing 312 generally in the central region 314 of the rear surface. According to one embodiment of the invention, printing 312 is provided using an ink which, if copied using a conventional color photocopier, will result in a photocopy which is altered in appearance with respect to the original printing 312. In one embodiment, the printing 312 is in a fluorescent or metallic ink, preferably a fluorescent orange ink which, when photocopied, appears as a purple or maroon color rather than an orange color.

Although there may be several types of inks which do not readily photocopy, it is believed that many such inks cannot readily be applied to thermal paper. Examples of inks which can be used, and which have been found to be useful for application to thermal paper, include neon pink PMS 805, neon yellow PMS 803 and neon green PMS 802. It should be understood that these represent examples of inks which may be used but are not intended to be an exhaustive listing.

In the embodiment of Fig. 3, the rear surface of the voucher also contains printing 316 which is positioned on or relatively close (such as within about $\frac{1}{4}$ inch, preferably within $\frac{1}{10}$ th inch of) the voucher edge 318a, 318b. Preferably, the edge printing 316 is also provided in an ink which is not readily photocopied without an alteration in appearance. In one embodiment, the edge printing 316 is in a color different from that of the central printing 312 and, in one embodiment, is provided in fluorescent yellow ink. In the depicted embodiment the central printing 312 is in a first (e.g. lateral) orientation, and the edge printing 316 is in an orientation which is at an angle (e.g. 90°) to the first orientation (e.g. vertical).

As described more fully below, it is preferred that some or all anti-counterfeiting features described herein can be provided as pre-printing or pre-providing (i.e. can be provided on the paper stock or paper supply 226 before it is fed to the printer 18). This is particularly useful in connection with providing the edge printing 316 relatively close to the edges 318a, b since close-to-edge printing is a feature which is difficult to reproduce with many inkjet, laser or other computer based printers (which often require a minimum space, such as a space no less than about $\frac{1}{4}$ inch, between the paper edge and printing provided by such printer).

In the embodiment depicted in Figs. 3A and 3B, certain visible features on the front and rear surfaces are registered, such that they occur in a predetermined spatial relationship on the front and rear surfaces. In the embodiment of Figs. 3A and 3B, printed rectangles 324a, 324b on the rear surface are aligned with indicia (in this case, star logos) 326a,b,c,d on the front surface. Preferably the printing of the indicia 326a,b,c,d on the front surface is of such a nature that it is at least partially visible when viewing the rear surface, such as when the voucher is held up to the light or otherwise backlit in such a fashion that the indicia 326a, 326c appear to be registered within the box 324a when viewing the rear surface. Preferably, the registration is of a nature (such as providing for relatively close sizing and spacing of the logos 326 as compared to the boxes 324) such that even relatively small misregistration (i.e. in which the printing on the front surface is not precisely aligned with corresponding printing on the rear surface) is readily detectable by visual inspection. This feature is useful because it is relatively difficult to use photocopying, inkjet or laser printer technology for providing printing on two opposite surfaces of a page or paper such that the printing on the opposite surfaces are closely registered (e.g. within about 1/8 inches). Preferably, according to the present invention, such opposite-surface printing provides registration on the front and rear surfaces which are mis-registered in either a longitudinal or vertical direction by no more than about 1/8 inches, preferably no more than about 1/16 inches and more preferably no more than about 1/32 inches.

In the embodiment of Figs. 3A and 3B, a pattern of perforations 332 is visible on both surfaces of the voucher. When perforations are used for purposes such as facilitating tearing or separation of paper segments, such perforations are typically in straight lines or a series of straight line segments. According to an embodiment of the present invention, perforations are provided in a pattern which includes some portions which having a curved appearance (even though each individual perforation may itself be straight) such as depicted in Figs. 3A and 3B. Such curved-pattern perforations are believed to be useful since they are readily visibly verified and relatively difficult for a counterfeiter to copy or reproduce. Preferably, the curved pattern includes portions 334 which have a relatively small radius of curvature such as radius of curvature of less than about 1/2 inch, preferably less than about 1/4 inch. In one embodiment, the perforations are

micro-perforations, such that each perforation has a length of about 0.4mm, a width of about 0.01mm, and an inter-perforation spacing of about 0.2mm.

5 In one embodiment, regions or indicia are preprinted 342 using an ink or other substance which preferably is substantially non-apparent or invisible (such as having a color, reflectivity, texture and the like closely matching that of the unprinted paper), but which, when rubbed or scratched with the edge of a coin, will cause minute amounts of the coin to rub off and adhere only to the printed portion, leaving a visible mark (indicated in Fig. 3 by phantom lines 342). In one embodiment, such indicia are provided by printing using an ink which includes titanium oxide. Thus, it is typically difficult for a would-be
10 counterfeiter to know which indicia should be printed in such non-visible ink since the indicia which are printed in a valid voucher are not readily apparent. However, the voucher may be relatively easily validated using only a ordinarily-available coin, i.e. without the use of special equipment.

Although it is possible to provide perforation of the type described as part of the paper stock 226, in one embodiment, the pattern of perforations is provided in conjunction
15 with the process of printing the value of the voucher using the printer 224. As depicted in Fig. 4, in one embodiment as the paper, following the printing, leaves the printer 224, the paper moves from a first exit position 412 and is conveyed, e.g. by pinch rollers 414a, 414b across the edge of a perforating roller 416 whose edge has, radially protruding therefrom, a plurality of perforation-producing punches or spikes 418. As depicted in Fig.
20 4, the punches 418 are positioned on the edge of the roller 416 in a manner to produce the desired perforation pattern (in the depicted embodiment, in a sinusoidal or wave-like pattern corresponding to the pattern depicted in Figs. 3A and 3B). The paper 412 is thus continuously perforated along its edge as it is conveyed toward a downstream position 422 and, eventually, dispensed to the user. In order to provide the proper rate of rotation
25 424 of the roller 416 as the paper is moved 426, the rate of rotation 424 of the roller 416 can be controlled and coordinated with the rate of paper movement 426 by a gear train, one or more motor controllers or other coordinator 228 in a manner that will be well known to those of skill in the art after understanding the present disclosure. The roller
30 416 can also be freewheeling, with rotation being driven by the paper movement. Although the perforation is described as occurring upon exit of the paper from the printer,

the perforating wheel could also be positioned to provide perforation to the paper as it enters the printer or at other locations that will be apparent to those of skill in the art upon understanding the present disclosure.

5 In one embodiment, some or all of a unit of the paper supply 226 (such as each roll of thermal paper) is associated with one or more serial numbers or other identifying numbers. In the embodiment of Fig. 5, the paper is preprinted, along the edge of the front surface, with such serial number or serial numbers. In the depicted embodiment, a single serial number is associated with a roll of thermal paper and this number is printed at spaced intervals in a vertical fashion near an edge of the voucher, preferably within less
10 than $\frac{1}{4}$ inch of the edge (similar to the manner described above in connection with the back surface edge printing 316 depicted in connection with Fig. 3B). In order to provide for ease of verifying the validity of the serial number, by the voucher redeemer, the serial number (or serial numbers) associated with the paper supply is also printed by the coin discriminator printer 18, e.g. substantially at the time the voucher value 514 is printed.
15 In one embodiment, when service personnel load a roll of paper into the paper supply unit 226, such personnel also enter the serial number associated with the roll into the computer 46, e.g. using an I-O device such as a keyboard, touch screen, or similar device 232. In this way, the computer 46 has the information needed to control the printer 18 so as to print an identifier number 516 on the face of the voucher which will match the preprinted
20 serial numbers 512 on the paper stock to permit the grocery store clerk or other redeemer to easily visually verify a match between the preprinted serial number 512 and the discriminator-printed serial number 516.

Although Fig. 5 depicts an embodiment in which a single serial number is associated with a unit of paper stock and is identically printed at intervals 512a, 512b,
25 512c, it is also possible to provide for identifying numbers which are preprinted on the paper stock, but which change along the length of a voucher or from one voucher to the next, such as incrementing by one or by some other number, or so as to change in some other manner (e.g. which is likely to be substantially unpredictable by a would-be counterfeiter). In this embodiment, it will be necessary for the computer 46 to be able to
30 calculate or detect which preprinted serial number will be positioned near the area where the discriminator-printed number 516 will be printed so that the computer 46 can control

the printer 18 to print a number 516 which will match the closest (or next preceding or succeeding) pre-printed serial number 512b. For example, the printer 18 may be configured to inform the computer 46 of the number of inches of thermal paper that has been thus-far dispensed from the roll. If it is known how the preprinted numbers 512 change along the length of the roll (such as incrementing by one for every inch of thermal paper dispensed) the computer 46 will have sufficient information to calculate, in a manner which will be well known to those of skill in the art after understanding the present disclosure, what number to print, using the printer 18, so as to match the closest or next succeeding or preceding preprinted number.

In light of the above description, a number of advantages of the present invention can be seen. The present invention provides devices and procedures which facilitate reducing, eliminating, deterring and/or detecting attempts at unauthorized duplication and/or counterfeiting of vouchers. The present invention provides counterfeiting detection features which can be relatively readily implemented such as requiring little or no hardware and/or software modification, and, in some embodiments, requiring only the use of paper or paper stock having one or more of the features as described herein, and, in this manner, at least some features of the present invention can be retrofit, i.e. implemented readily in existing coin discriminators. The present invention provides at least some anti-counterfeiting or counterfeit detection features which use only, or primarily, visual inspection of the voucher and thus at least some features can be implemented without the need for modifying or adding hardware. At least some anti-counterfeiting or counterfeiting detection features can be performed relatively rapidly, such as verifying the correct color of various printing or indicia, correct positioning or registration, correct patterning or configuration of perforations and the like), preferably without requiring the redeemer to flip or rotate the voucher or otherwise manipulate the voucher, or enter data or otherwise handle the voucher (other than, e.g. to hold it up to ordinary light) such that at least some anti-counterfeiting or counterfeit detection features of the present invention can be implemented without substantial delay at a checkout lane. In some embodiments, certain features of the invention are not readily apparent upon visual inspection of a valid voucher and thus would-be counterfeiters may find it difficult to reproduce such features. For example, in one embodiment, at least some indicia are

provided which fluoresce or have other visible characteristics only when exposed to ultraviolet or other special light. According to one embodiment, at least some indicia are provided which are substantially invisible until rubbed or scraped with a coin or similar object. Preferably in some embodiments the voucher is provided with features which are not readily reproduced or counterfeited without using devices or procedures which are typically not available to the general public. For example, perforations which are patterned in a curved, preferably tightly radiused pattern which preferably provides a periodic, smooth and/or repeating pattern and preferably is made using relatively small perforations are typically difficult to provide without special, not-readily-available, equipment.

A number of variations and modifications of the invention can also be used. It is possible to use some features of the invention without using others. For example, it is possible to use non-photocopying inks without using micro perforations, or it is possible to use front/back registered marks without using close-to-the-edge printing. Although the present invention has been described in connection with avoiding, preventing or detecting unauthorized duplication or counterfeiting of a coin-discriminator voucher, the present invention can also be used in connection with avoiding unauthorized duplication or counterfeiting of other items such as coupons, checks, tickets (such as airline, subway or other transportation tickets, game, performance, concert or other event tickets, and the like) negotiable instruments and the like. Although some features of the invention have been described as capable of implementation using a computer, it is possible to use other devices in place of a computer such as one or more application specific integrated circuits (ASIC's) hardwired and/or discrete circuitry, and the like. Although embodiments relating to paper stock serial numbers were described as involving manual entry of serial numbers into the computer, it is also possible to provide for serial number entry by partially or fully automatic scanning or detection, such as using bar code scanners, magnetic ink detectors and the like. Although it is believed many other coin discriminators may involve the use of thermal printers, the present invention can be used in connection with many types of printers including laser printers, inkjet printers, dot matrix printers, line (impact) printers and the like. Although front/back surface registration of a pair of logos and a box was depicted, many shapes or symbols can be used for verifying registration. Although

embodiments have been described which involve pre-printing or pre-providing certain items, it is also possible to use one or more printers housed in the coin discriminator device to print anti-counterfeiting items, such as printing in a fashion and/or with an ink which produces an altered appearance in a photocopy made therefrom.

5 The present invention, in various embodiments, includes components, methods, processes, systems and/or apparatus substantially as depicted and described herein, including various embodiments, subcombinations, and subsets thereof. Those of skill in the art will understand how to make and use the present invention after understanding the present disclosure. The present invention, in various embodiments, includes providing
10 devices and processes in the absence of items not depicted and/or described herein or in various embodiments hereof, including in the absence of such items as may have been used in previous devices or processes, e.g. for improving performance, achieving ease and/or reducing cost of implementation.

 The foregoing discussion of the invention has been presented for purposes of
15 illustration and description. The foregoing is not intended to limit the invention to the form or forms disclosed herein. Although the description of the invention has included description of one or more embodiments and certain variations and modifications, other variations and modifications are within the scope of the invention, e.g. as may be within the skill and knowledge of those in the art, after understanding the present disclosure. It
20 is intended to obtain rights which include alternative embodiments to the extent permitted, including alternate, interchangeable and/or equivalent structures, functions, ranges or steps to those claimed, whether or not such alternate, interchangeable and/or equivalent structures, functions, ranges or steps are disclosed herein, and without intending to publicly dedicate any patentable subject matter.

WHAT IS CLAIMED IS:

1. A method for providing a voucher in a coin discriminator, having a discriminator printer, with the voucher configured to assist in distinguishing unauthorized duplicate or counterfeit vouchers, the method comprising the steps of:

5 providing a computer coupled to said printer and an i/O device coupled to said computer;

printing at least first language on a thermal paper substrate, oriented in a first direction, using a fluorescent ink such that said first language has a first appearance on said thermal paper substrate but wherein a photocopy of first language has a second appearance, different from said first appearance;

10 printing at least second language oriented in a directions about 90 degrees to said first direction positioned less than 0.25 inches from an edge of said thermal paper substrate;

placing a substantially non-visible mark on said thermal paper substrate using a first marking medium;

15 wherein said thermal paper substrate has marked thereon, at least an initial serial number identifying a unit of said thermal paper substrate;

loading said unit of said thermal paper substrate into a position from which thermal paper substrate in said unit can be fed to said discriminator printer;

20 inputting said serial number into said computer using said i/O device;

using said discriminator printer to print, on said thermal paper substrate, at least first indicia containing an indication of a value of said voucher;

printing a number related to said serial number on said thermal paper substrate;

25 providing a plurality of perforations in said medium to define a first curved pattern of microperforations which includes a region defining a radius of curvature less than about 0.5 inches; and

rubbing said non-visible mark with a coin wherein portions of said coin adhere to said non-visible mark to render said mark visible.

2. A method for providing a voucher in a coin discriminator, having a discriminator printer, with the voucher configured to assist in distinguishing unauthorized duplicate or counterfeit vouchers, the method comprising the steps of:

placing visible marks on a first substrate using a marking medium which has a first appearance on said substrate but wherein a photocopy of said visible marks has a second appearance, different from said first appearance; and

using said discriminator printer to print, on said substrate, at least first indicia containing an indication of a value of said voucher.

3. A method as claimed in claim 2 wherein said substrate is paper.

4. A method as claimed in claim 2 wherein said substrate is thermal paper.

5. A method as claimed in claim 2 wherein said marking medium is fluorescent ink.

6. A method for providing a voucher in a coin discriminator, having a discriminator printer, with the voucher configured to assist in distinguishing unauthorized duplicate or counterfeit vouchers, the method comprising the steps of:

placing visible marks on a first substrate using a fluorescent marking medium; and

using said discriminator printer to print, on said substrate, at least first indicia containing an indication of a value of said voucher.

7. A method for providing a voucher in a coin discriminator, having a discriminator printer, with the voucher configured to assist in distinguishing unauthorized duplicate or counterfeit vouchers, the method comprising the steps of:

placing visible marks on a first substrate positioned less than 0.25 inches from an edge of said medium; and

using said discriminator printer to print, on said substrate, at least first indicia containing an indication of a value of said voucher.

8. A method for providing a voucher in a coin discriminator, having a discriminator printer, with the voucher configured to assist in distinguishing unauthorized duplicate or counterfeit vouchers, the method comprising the steps of:

printing at least first language on said substrate, oriented in a first direction and second language oriented in a direction at a first angle to said first direction; and

using said discriminator printer to print, on said substrate, at least first indicia containing an indication of a value of said voucher.

5 9. A method as claimed in claim 8 wherein said angle is about 90 degrees.

10 10. A method for providing a voucher in a coin discriminator, having a discriminator printer, with the voucher configured to assist in distinguishing unauthorized duplicate or counterfeit vouchers, the method comprising the steps of:

 using said discriminator printer to print, on a substrate, at least first indicia containing an indication of a value of said voucher; and

 providing a plurality of perforations in said substrate to define a first curved pattern of perforations.

 11. A method as claimed in claim 10 wherein said first curved pattern includes a region defining a radius of curvature less than about 0.5 inches.

15 12. A method as claimed in claim 10 wherein said perforations are microperforations.

 13. A method for providing a voucher in a coin discriminator, having a discriminator printer, with the voucher configured to assist in distinguishing unauthorized duplicate or counterfeit vouchers, the method comprising the steps of:

20 placing a substantially non-visible mark on a first substrate using a first marking medium;

 using said discriminator printer to print, on said substrate, at least first indicia containing an indication of a value of said voucher; and

25 rubbing said non-visible mark with a coin wherein portions of said coin adhere to said non-visible mark to render said mark visible.

 14. A method as claimed in claim 13 wherein said first marking medium comprises white ink containing titanium oxide.

15. A method for providing a voucher in a coin discriminator, having a discriminator printer, with the voucher configured to assist in distinguishing unauthorized duplicate or counterfeit vouchers, the method comprising the steps of:

5 placing a series of identifier symbols on a first substrate, said series of identifier symbols being spaced from one another; and

using said discriminator printer to print, on said substrate, at least first indicia containing an indication of said identifier.

16. A method as claimed in claim 15 wherein said identifier symbols include a serial number identifying a unit of said substrate.

10 17. A method as claimed in claim 16 further comprising providing a computer coupled to said printer and an i/O device coupled to said computer and inputting said serial number into said computer using said i/O device.

18. A method as claimed in claim 15 wherein at least some of said series of identifier symbols are different from one another.

15 19. A method as claimed in claim 18 wherein said series of identifier symbols include a series of numbers which increment by a predetermined amount.

20. A voucher for dispensing from a coin discriminator comprising:

a thermal paper substrate;

at least a first fluorescent ink region printed on a surface of said substrate; and

20 a plurality of microperforations through said substrate defining at least a first curved pattern.

21. Apparatus for use in outputting results from a coin discriminator having a discriminator printer, with the voucher configured to assist in distinguishing unauthorized duplicate or counterfeit vouchers, comprising:

25 a computer coupled to said printer;

a thermal paper substrate having

at least first language printed on said substrate, oriented in a first direction, using a fluorescent ink such that said first language has a first

appearance on said thermal paper substrate but wherein a photocopy of first language has a second appearance, different from said first appearance;

5 at least second language printed on said substrate oriented in a direction about 90 degrees to said first direction positioned less than 0.25 inches from an edge of said thermal paper substrate;

 a substantially non-visible mark on said thermal paper substrate wherein when said non-visible mark is rubbed with a coin, portions of said coin adhere to said non-visible mark to render said mark visible;

10 wherein said thermal paper substrate has marked thereon, at least an initial serial number identifying a unit of said thermal paper substrate;

 said thermal paper substrate located in a position from which thermal paper substrate can be fed to said discriminator printer;

 i/O means for inputting said serial number into said computer;

15 means for controlling said discriminator printer to print, on said thermal paper substrate, at least first indicia containing an indication of a value of said voucher;


 means for controlling said discriminator printer to print a number related to said serial number on said thermal paper substrate; and



20 a plurality of perforations in said medium defining a first curved pattern of microperforations which includes a region defining a radius of curvature less than about 0.5 inches.

22. A method for providing a secure voucher substantially as described and depicted herein.

23. A secure voucher substantially as described and depicted herein.

25 24. A coin discriminator substantially as described and depicted herein.





38a —

318b

318b

318a

312

316

324b

324b

342

324

324a

312

314

332

COINSTAR

Qualification at
370000000

Lab
Test: Test
VOID-VOID-VOID

Number of Coins Counted:
Quarters: 1
Dimes: 1
Nickels: 1
Pennies: 1
Gold Total: 21.69
Processing Fee: 30.13

\$1.50
Cash Value

Redeem at any Cashier
at the above store
Please redeem today.

Transaction 25001
Mon Oct 15 08:08:27 1998

Thanks for shopping at:

GIANT EAGLE

324b

Customer: RENE CH
PLU 9086

0-00000-09086-9

----- Tear Here -----

PRO BOWL CONTEST

Let's PRINT the
information below and
mail/drop off entry to:

PRO BOWL SWEEPSTAKES
c/o COINSTAR
1521 SE 36th St.
Bellevue, WA 98006

Name: _____

Address: _____

City: _____

State: _____

Phone: _____

NO PURCHASE NECESSARY
One entry per envelope.
You do not have to be
present to win. Prizes
posted on machine.

Entries must be received
at above address by 4PM.
1/24/97 to be eligible
for grand prize and by
4PM 1/27/97 to be
eligible for runner-up
prizes. Odds of winning
depend on number of
entries received.

Fig 3A

Fig 3B



at
Your SuperMarket
99990001
23 Main Street
Anytown, CA 98006
USA

Number of Coins Counted:
Quarters: 0
Dimes: 0
Nickels: 2
Pennies: 6
Coin Total: \$0.16
Processing Fee: \$0.01


In a voucher is worth

\$0.15
Cash Value

Redeem at any Cashier
at the above store.
Please redeem today.

Transaction #1053
Thu Oct 8 06:59:18 1998

Thanks for shopping at



5-01053-00015-2

----- Tear Here -----



AIRTOUCH
Cellular

2 MONTHS OF BASIC
VOICE MAIL

Valid for TWO months of
basic voice mail with
new activation.

Valid anytime. Not valid
holidays & subject to
rules of use. Not valid
with other discount
offers unless specified.

Coupon VOID if
purchased, sold, or
bartered for cash.

VALID THROUGH 11/1/98

Merchant On: 7:
(614)836-7283

Copyright 1998
Entertainment
Publications Inc.

----- Tear Here -----

SAVE ANOTHER \$10
in change and GET
MORE BONUS OFFERS!

244

INTERNATIONAL SEARCH REPORT

International application No.
PCT/US99/24895

A. CLASSIFICATION OF SUBJECT MATTER

IPC(6) : G06K 15/00

US CL : 358/1.14, 1.18

According to International Patent Classification (IPC) or to both national classification and IPC

B. FIELDS SEARCHED

Minimum documentation searched (classification system followed by classification symbols)

U.S. : 358/1.1, 1.14, 1.18; 705/13, 401, 405; 232/7; 700/231, 233

Documentation searched other than minimum documentation to the extent that such documents are included in the fields searched

Electronic data base consulted during the international search (name of data base and, where practicable, search terms used)

C. DOCUMENTS CONSIDERED TO BE RELEVANT

Category*	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
A,P	US 5,917,996 A (THORPE) 29 June 1999, see entire document.	1-24
A,P	US 5,835,689 A (BRAUN et al) 10 November 1998, see entire document.	1-24
A	US 4,977,502 A (BAKER et al) 11 December 1990, see entire document.	1-24

☐ Further documents are listed in the continuation of Box C.
 ☐ See patent family annex.

* Special categories of cited documents:	*T* later document published after the international filing date or priority date and not in conflict with the application but cited to understand the principle or theory underlying the invention
A document defining the general state of the art which is not considered to be of particular relevance	*X* document of particular relevance; the claimed invention cannot be considered novel or cannot be considered to involve an inventive step when the document is taken alone
B earlier document published on or after the international filing date	*Y* document of particular relevance; the claimed invention cannot be considered to involve an inventive step when the document is combined with one or more other such documents, such combination being obvious to a person skilled in the art
L document which may throw doubts on priority claim(s) or which is cited to establish the publication date of another citation or other special reason (as specified)	*G* document member of the same patent family
O document referring to an oral disclosure, use, exhibition or other means	
P document published prior to the international filing date but later than the priority date claimed	

Date of the actual completion of the international search

19 DECEMBER 1999

Date of mailing of the international search report

12 JAN 2000

Name and mailing address of the ISA/US
Commissioner of Patents and Trademarks
Box PCT
Washington, D.C. 20231

Facsimile No. (703) 305-3230

Authorized officer

ART EVANS

Telephone No. (703) 308-0000



INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(51) International Patent Classification ⁶ : G06K 15/00		A1	(11) International Publication Number: WO 00/25260
			(43) International Publication Date: 4 May 2000 (04.05.00)
(21) International Application Number: PCT/US99/24895		(81) Designated States: AE, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BY, CA, CH, CN, CU, CZ, DE, DK, EE, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MD, MG, MK, MN, MW, MX, NO, NZ, PL, PT, RO, RU, SD, SE, SG, SI, SK, SL, TJ, TM, TR, TT, UA, UG, UZ, VN, YU, ZA, ZW, ARIPO patent (GH, GM, KE, LS, MW, SD, SL, SZ, TZ, UG, ZW), Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European patent (AT, BE, CH, CY, DE, DK, ES, FI, FR, GB, GR, IE, IT, LU, MC, NL, PT, SE), OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, GW, ML, MR, NE, SN, TD, TG).	
(22) International Filing Date: 21 October 1999 (21.10.99)			
(30) Priority Data: 60/105,508 23 October 1998 (23.10.98) US			
(71) Applicant: COINSTAR, INC. [US/US]; 1800 114th Avenue S.E., Bellevue, WA 98004 (US).			
(72) Inventors: GEIGER, Steven, M.; 6013 228th N.W., Stanwood, WA 98292 (US). BROWN, David, J.; 23333 S.E. 31st Street Court, Issaquah, WA 98027 (US). MANION, Timothy, J.; 4712 46th Avenue S.W., Seattle, WA 98116 (US). SCHERER, Scott, J.; 6139 West Colgate Avenue, Los Angeles, CA 90036 (US).			
(74) Agents: HUGHES, Richard, L. et al.; Sheridan Ross P.C., Suite 1200, 1560 Broadway, Denver, CO 80202-5141 (US).			


Published

With international search report.

(54) Title: COIN-DISCRIMINATOR VOUCHER ANTI-COUNTERFEITING METHOD AND APPARATUS

(57) Abstract

Anti-counterfeiting and counterfeit detection devices and procedures are provided particularly usable in connection with vouchers (5) issued by coin discriminator or coin counting machines. Paper stock (226) may be preprinted with inks which are not readily photocopied without apparent alteration. Preprinting is preferably in two or more orientations such as longitudinal and lateral and preferably some reprinting is positioned closer to the paper stock edge than can typically be achieved using ordinarily available laser printers or inkjet printers (18). A pattern of perforations, preferably micro perforations, are provided in a curved, preferably tightly radiused shape or configuration. Serial numbers (512c) or other identifiers may be reprinted on portions of the paper stock and matching or correlatable numbers printed on such preprinted paper stock substantially at the time of printing the voucher value. Patterns or indicia printed on one surface of the paper are preferably registered with respect to patterns or indicia printed on the opposite side such that a voucher may be validated by verifying proper registration such as when holding a voucher up to a light.



FOR THE PURPOSES OF INFORMATION ONLY

Codes used to identify States party to the PCT on the front pages of pamphlets publishing international applications under the PCT.

AL	Albania	ES	Spain	LS	Lesotho	SI	Slovenia
AM	Armenia	FI	Finland	LT	Lithuania	SK	Slovakia
AT	Austria	FR	France	LU	Luxembourg	SN	Senegal
AU	Australia	GA	Gabon	LV	Latvia	SZ	Swaziland
AZ	Azerbaijan	GB	United Kingdom	MC	Monaco	TD	Chad
BA	Bosnia and Herzegovina	GE	Georgia	MD	Republic of Moldova	TG	Togo
BB	Barbados	GH	Ghana	MG	Madagascar	TJ	Tajikistan
BE	Belgium	GN	Guinea	MK	The former Yugoslav Republic of Macedonia	TM	Turkmenistan
BF	Burkina Faso	GR	Greece	ML	Mali	TR	Turkey
BG	Bulgaria	HU	Hungary	MN	Mongolia	TT	Trinidad and Tobago
BJ	Benin	IE	Ireland	MR	Mauritania	UA	Ukraine
BR	Brazil	IL	Israel	MW	Malawi	UG	Uganda
BY	Belarus	IS	Iceland	MX	Mexico	US	United States of America
CA	Canada	IT	Italy	NE	Niger	UZ	Uzbekistan
CF	Central African Republic	JP	Japan	NL	Netherlands	VN	Viet Nam
CG	Congo	KE	Kenya	NO	Norway	YU	Yugoslavia
CH	Switzerland	KG	Kyrgyzstan	NZ	New Zealand	ZW	Zimbabwe
CI	Côte d'Ivoire	KP	Democratic People's Republic of Korea	PL	Poland		
CM	Cameroon	KR	Republic of Korea	PT	Portugal		
CN	China	KZ	Kazakhstan	RO	Romania		
CU	Cuba	LC	Saint Lucia	RU	Russian Federation		
CZ	Czech Republic	LI	Liechtenstein	SD	Sudan		
DE	Germany	LK	Sri Lanka	SE	Sweden		
DK	Denmark	LR	Liberia	SG	Singapore		
EE	Estonia						

COIN-DISCRIMINATOR VOUCHER ANTI-COUNTERFEITING METHOD AND APPARATUS

5 The present invention relates to the provision of vouchers in connection with a coin-discriminator and/or counter and in particular ways of deterring, reducing, eliminating or detecting unauthorized duplication or counterfeiting of vouchers.

BACKGROUND INFORMATION

10 At least some types of coin- discriminators are configured to receive a plurality of coins of various denominations, e.g. from untrained users (such as grocery store or other retail location customers), typically including non-coin items and/or foreign or other undesired coins, to discriminate the various denominations of the desired coins (possibly after separating non-coin items and/or undesired coins) to determine the value of the discriminated desired coins, and to output an indication of the value of the total amount
15 of the discriminated, desired coins. Although many forms of such value output may be termed a voucher, including paperless output (such as depositing a value in a user's bank account, e.g. after reading a user's bank card or other identifier), the present invention is particularly directed to devices which include apparatus or procedures for outputting a physical voucher such as a paper voucher with indicia indicating a value related to the
20 total amount of discriminated, desired coins. Although such physical vouchers will be discussed as "paper" voucher hereinbelow, its possible to provide physical vouchers in other forms such as with indicia placed on other substrates such as plastic, cardboard, magnetic or other non-visible information-bearing media and the like.

25 Because a physical or "paper" voucher has value, in the sense that it can be redeemed for, e.g. cash or credit, it is important for the redeemer to have confidence that a voucher which is presented for redemption is genuine, i.e. is not an unauthorized duplicate or counterfeit voucher. Verifying the genuineness of a voucher is especially difficult in the face of sophisticated image production, reproduction or manipulation technologies such as color photocopy technology, color scanning technologies, computer-
30 based printing technologies such as inkjet (including color inkjet) or laser (including color laser) printer, e.g. coupled to personal computers, work stations and the like. Accordingly, it would be useful to provide vouchers whose genuineness can be readily determined, as compared to an unauthorized duplicate or counterfeit voucher, e.g.

produced using such image duplication production, reproduction or manipulation technologies.

Some approaches to detecting unauthorized duplication or counterfeiting have involved encrypting certain information which is then printed on the voucher as part of the voucher printing procedure such that decryption provides a level of confidence that the voucher is genuine. One such procedure is described in U.S. Patent Application 09/178,441 (attorney file 3730-908), incorporated herein by reference. Although such encryption/decryption procedures can be quite useful (and, indeed, can, if desired, be used in combination with some or all features of the present invention), there are circumstances in which it may be desirable to provide for other counterfeit detection measures, in addition to or in place of such encryption/decryption measures.

In some circumstances, it may be desirable to provide anti-counterfeit measures or devices which are independent of the need for substantial modification of printing, check-out or verification software (of the type that might be used in connection with encryption/decryption). For example, it may be desired to avoid making modifications to printing software and/or to avoid modifying or providing software for decryption. Furthermore, in some circumstances it may be desired to avoid the personnel training or hardware involved in a decryption verification process. For example, in some circumstances it is desirable to permit the voucher redemption (which may typically occur at a grocery store or other retail location check-out stand) to be performed, in whole or in part, based on a visual inspection of the voucher (e.g. without the need to perform a decryption step). In some circumstances it may be desirable to provide for duplicate/counterfeit detection without the need for using a computer or other equipment.

Many self-service coin-discriminators of a type with which the present invention may be used employ a thermal printer for outputting a paper voucher. Thermal printers can be particularly useful because of the lack of a requirement to replenish ink or toner. Thermal printers typically operate in conjunction with a type of paper specific to thermal printing ("thermal paper"). Thermal paper often has characteristics which limit how the paper may be treated (e.g. limiting the types of ink or other materials that may be used in connection with providing, for example background preprinting, watermarks and the like). Accordingly, it would be useful to provide voucher duplication/counterfeiting detection

or prevention which can be reasonably and feasibly used with thermal papers and/or thermal printers (e.g. without incurring relatively high costs).

5 Although there are benefits to an anti-counterfeiting system which provides for detection of unauthorized duplications or counterfeits (at least in part) using a visual inspection of the voucher, a system in which all anti-counterfeiting features are features which are normally visible also means that potential counterfeiters can determine what features need to be copied or duplicated by performing a visual inspection of a valid voucher. Accordingly, it would be useful, in some embodiments, to provide at least some anti-counterfeiting features which are not normally visible, i.e. which are not visible in
10 ordinary ambient light of a redemption location.

Because, in at least some systems, voucher redemption is performed at a retail location, such as during ordinary retail purchase "check out", it would be useful to provide anti-counterfeiting procedures or devices which can be performed relatively rapidly so as to avoid checkout line delays. For example, it would be useful if some or all anti-
15 counterfeiting features can be used for verification without the need for special positioning or manipulation of a voucher and/or without the need for manually inputting features or information from the voucher and preferably without the need to provide special equipment for voucher verification at checkout locations.

In situations where coin-discriminators are already being used, it would be useful
20 to provide for voucher anti-counterfeiting measures which include features that can be provided with little or no modification of coin-discriminator hardware and/or retail location check-out hardware. In some embodiments, it would be useful to provide at least some anti-counterfeiting features which can be implemented by loading paper into already-existing coin-discriminators and substantially without modification of coin-discriminator
25 hardware.

SUMMARY OF THE INVENTION

The present invention includes at least one and preferably a plurality of features provided in or on paper (or other substrate) used for printing a voucher. In one
30 embodiment, at least some portions of the paper are pre-printed or otherwise pre-provided (i.e. printed or provided prior to the printing or providing of indicia indicating the value

of the voucher) in ink which is not readily reproducible by ordinary color photocopiers, such as certain fluorescent inks. In one embodiment, the paper (or other substrate) is provided with a plurality of perforations in a pattern which is not readily reproducible such as a pattern including curved or otherwise non-linear patterns of perforation preferably with the perforations being relatively small and closely spaced and the pattern defining relatively tight-radiused but preferably substantially continuous curves.

In one embodiment, the voucher is provided with printing on both surfaces which are registered relative to one another in such a fashion that the registration may be readily verified (e.g. by holding the voucher up to a light or otherwise backlighting a voucher so as to view at least some portions of printing on the two surfaces simultaneously). In some embodiments, portions of the voucher are printed with a material which has relatively low visibility, or is substantially invisible, until such portion is treated or manipulated, e.g. such as by rubbing or scratching with a coin or other object.

Preferably at least two or more anti-counterfeiting features of a voucher can be verified by viewing only one surface of the voucher, i.e. without the need to flip the voucher over to view the opposite side.

In some embodiments, some or all features are features which permit voucher verification using only visual inspection of the voucher, i.e. without the need to use any equipment. In other embodiments, at least one feature is a feature which is not readily apparent in ordinary or typical light (so as to render it difficult for a potential counterfeiter to even be aware of, much less to duplicate, such feature) such as providing markings which fluoresce or otherwise have detectable properties when viewed in specific types of light such as ultraviolet light.

In some embodiments, the voucher paper is preprinted or preprovided with indicia which are oriented in different fashions (such as both vertically and horizontally) and/or are positioned near the edge of the paper or are otherwise oriented or positioned in a fashion which may be difficult to duplicate with typical computer-based printers.

BRIEF DESCRIPTION OF THE DRAWINGS

Fig. 1 is a perspective view of a coin-discriminating device, in an opened configuration, of a type which may be used in at least one implementation of the present invention;

5 Fig. 2 is a block diagram depicting certain components of a coin discriminator of a type which can be used in accordance with implementation of the present invention;

Fig. 3A is a front view of a voucher of a type which may be used according to one embodiment of the present invention;

10 Fig. 3B is a view of the back surface of the voucher of Fig. 3A with Fig. 3B being positioned in alignment with Fig. 3A to show relative locations of features on opposite surfaces;

Fig. 4 is a partial perspective view of a perforation wheel according to an embodiment of the present invention; and

15 Fig. 5 is a front view of a voucher according to one embodiment of the present invention.

DETAILED DESCRIPTION OF THE PREFERRED EMBODIMENT

20 Fig. 1 is a perspective view of a coin-discriminator of a type which can be used in connection with embodiments of the present invention. The embodiment depicted in Fig 1 generally includes a coin counting/sorting portion 12, a voucher dispensing portion 14a and a coupon dispensing portion 14b. In the depicted embodiment, the coin counting portion 12 includes an input tray 16, a coin return region 22, and customer I/O devices, including a keyboard 24, additional keys 26, a speaker 28 and a video screen 32. The apparatus can include various indicia, signs, displays, advertisement and the like on its

25 external surfaces. A power cord 34 provides power to the mechanism.

Preferably, when the doors 36a, 36b are in the open position as shown, most or all of the components are accessible for cleaning and/or maintenance. In the depicted embodiment, a voucher printer 18 is mounted on the inside of the door 36a. A number of printers can be used for this purpose. In one embodiment, a model KLDS0503 printer, available from Axiohm is used. The right-hand portion of the cabinet includes a coupon

30 feeder 42 for dispensing, e.g., pre-printed manufacturer coupon sheets through a chute

44 to a coupon hopper on the outside portion of the door 36b. A computer 46, in the depicted embodiment, is positioned at the top of the right hand portion of the cabinet in order to provide a relatively clean, location for the computer. An I/O board 48 is positioned adjacent the sheet feeder 42.

5 The general coin path for the embodiment depicted in Fig 1 is from the input tray 16, down first and second chutes to a trommel 52, to a coin pickup assembly 54, along a coin rail 56 and past a sensor 58. If, based on sensor data, it is determined that the coin can and should be accepted, a controllable deflector door 62 is activated to divert coins from their gravitational path to coin tubes 64a, b for delivery to coin trolleys 66a, b. If
10 it has not been determined that a coin can and should be accepted, the door 62 is not activated and coins (or other objects) continue down their gravitational or default path to a reject chute 68 for delivery to a customer-accessible reject or return box 22.

 In use, a user is provided with instructions such as on computer screen 32. The user places a mass of coins, typically of a plurality of denominations (typically
15 accompanied by dirt or other non-coin objects) in the input tray 16. The user is prompted to push a button to inform the machine that the user wishes to have coins discriminated. Thereupon, the computer causes an input gate (not shown) to open and provides a signal to prompt the user to begin feeding coins. When the gate is open, a motor is activated to begin rotating the trommel assembly 52. The user moves coins over the peaked output
20 edge 72 of the input tray 16, typically by lifting or pivoting the tray by handle 74, and/or manually feeding coins over the peak 72. The coins pass the gate (typically set to prevent passage of more than a predetermined number of stacked coins, such as by defining an opening equal to about 3.5 times a typical coin thickness). Instructions on the screen 32 may be used to tell the user to continue or discontinue feeding coins, can relay the status
25 of the machine, the amount counted thus far, provide encouragement or advertising messages and the like. The coin rail 56 functions to receive coins output by the coin pickup assembly 54, and transports the coins in a singulated (one-at-a-time) fashion past the sensor 58 to the diverting door 62. Once no more coins are detected and/or in response to user input, the system determines that the transaction is complete and the
30 computer 46 will send instructions to the printer 18 causing the printer to output a voucher of a type which may be exchanged for goods, services or cash.

Fig. 2 is a block diagram of a coin-discriminator of a type which can be used in accordance with implementations of the present invention. Some of the items in Fig. 2 correspond to components in the device of Fig. 1. In operation, an untrained user, such as a grocery store or other retail location customer places a plurality of coins of unknown value and random orientation in a receiving tray or other receiving area 16. Typically, foreign or other undesirable coins and foreign objects such as currency or other paper, paper clips, lint, keys and the like are mixed with the desired coins and placed, such as being poured or dumped, substantially all at once, into the tray 16. A conveyance device 214, such as a chute, trough, slide or the like, or including positive drive or otherwise moving conveyances such as conveyer belts, Archimedes' screws and the like, are used to provide at least some of the desired coins from the receiving area 16 to a coin-discriminator 218. Preferably, prior to entry to the discriminator 218, at least some of the foreign objects or materials are separated such as using airflow, vacuum, gravitational separation, size-based separation (such as through openings of predetermined size or sizes) and the like. The discriminator 216 provides a signal to a calculating device, preferably a computer with sufficient information regarding the number of desired coins of various denominations such that the computer 46 can output or store a value equal to or related to (such as being a predetermined amount or portion less than) the value of the desired discriminated coins which are then placed in one or more bins 66 or other receiving regions. The computer 46, at the end of a transaction (as indicated by lack of further input of coins for a predetermined period and/or input from a user) controls a paper voucher printer 18 to print, on paper (or other substrates) obtained from a roll of paper or other paper supply 226 a redeemable voucher for an amount related to the total value of the discriminated desired coins for this transaction.

Figs. 3A and 3B depict a number of features of a voucher useful for avoiding, preventing and/or detecting unauthorized duplication or counterfeiting of vouchers. Figs. 3A and 3B are presented herein in a fashion which indicates the relative positions of the indicia or marking on the front surface (Fig 3A) and the opposite or rear surface (Fig. 3B). I.e., features which are shown as aligned in corresponding locations in Figs. 3A and 3B are features which would appear at corresponding longitudinal positions on opposite surfaces of the voucher.

In the depicted embodiment, the rear surface (Fig. 3B) of the voucher includes printing 312 generally in the central region 314 of the rear surface. According to one embodiment of the invention, printing 312 is provided using an ink which, if copied using a conventional color photocopier, will result in a photocopy which is altered in appearance with respect to the original printing 312. In one embodiment, the printing 312 is in a fluorescent or metallic ink, preferably a fluorescent orange ink which, when photocopied, appears as a purple or maroon color rather than an orange color.

Although there may be several types of inks which do not readily photocopy, it is believed that many such inks cannot readily be applied to thermal paper. Examples of inks which can be used, and which have been found to be useful for application to thermal paper, include neon pink PMS 805, neon yellow PMS 803 and neon green PMS 802. It should be understood that these represent examples of inks which may be used but are not intended to be an exhaustive listing.

In the embodiment of Fig. 3, the rear surface of the voucher also contains printing 316 which is positioned on or relatively close (such as within about $\frac{1}{4}$ inch, preferably within $\frac{1}{10}$ th inch of) the voucher edge 318a, 318b. Preferably, the edge printing 316 is also provided in an ink which is not readily photocopied without an alteration in appearance. In one embodiment, the edge printing 316 is in a color different from that of the central printing 312 and, in one embodiment, is provided in fluorescent yellow ink. In the depicted embodiment the central printing 312 is in a first (e.g. lateral) orientation, and the edge printing 316 is in an orientation which is at an angle (e.g. 90°) to the first orientation (e.g. vertical).

As described more fully below, it is preferred that some or all anti-counterfeiting features described herein can be provided as pre-printing or pre-providing (i.e. can be provided on the paper stock or paper supply 226 before it is fed to the printer 18). This is particularly useful in connection with providing the edge printing 316 relatively close to the edges 318a, b since close-to-edge printing is a feature which is difficult to reproduce with many inkjet, laser or other computer based printers (which often require a minimum space, such as a space no less than about $\frac{1}{4}$ inch, between the paper edge and printing provided by such printer).

In the embodiment depicted in Figs. 3A and 3B, certain visible features on the front and rear surfaces are registered, such that they occur in a predetermined spatial relationship on the front and rear surfaces. In the embodiment of Figs. 3A and 3B, printed rectangles 324a, 324b on the rear surface are aligned with indicia (in this case, star logos) 326a,b,c,d on the front surface. Preferably the printing of the indicia 326a,b,c,d on the front surface is of such a nature that it is at least partially visible when viewing the rear surface, such as when the voucher is held up to the light or otherwise backlit in such a fashion that the indicia 326a, 326c appear to be registered within the box 324a when viewing the rear surface. Preferably, the registration is of a nature (such as providing for relatively close sizing and spacing of the logos 326 as compared to the boxes 324) such that even relatively small misregistration (i.e. in which the printing on the front surface is not precisely aligned with corresponding printing on the rear surface) is readily detectable by visual inspection. This feature is useful because it is relatively difficult to use photocopying, inkjet or laser printer technology for providing printing on two opposite surfaces of a page or paper such that the printing on the opposite surfaces are closely registered (e.g. within about 1/8 inches). Preferably, according to the present invention, such opposite-surface printing provides registration on the front and rear surfaces which are mis-registered in either a longitudinal or vertical direction by no more than about 1/8 inches, preferably no more than about 1/16 inches and more preferably no more than about 1/32 inches.

In the embodiment of Figs. 3A and 3B, a pattern of perforations 332 is visible on both surfaces of the voucher. When perforations are used for purposes such as facilitating tearing or separation of paper segments, such perforations are typically in straight lines or a series of straight line segments. According to an embodiment of the present invention, perforations are provided in a pattern which includes some portions which having a curved appearance (even though each individual perforation may itself be straight) such as depicted in Figs. 3A and 3B. Such curved-pattern perforations are believed to be useful since they are readily visibly verified and relatively difficult for a counterfeiter to copy or reproduce. Preferably, the curved pattern includes portions 334 which have a relatively small radius of curvature such as radius of curvature of less than about 1/2 inch, preferably less than about 1/4 inch. In one embodiment, the perforations are

micro-perforations, such that each perforation has a length of about 0.4mm, a width of about 0.01mm, and an inter-perforation spacing of about 0.2mm.

5 In one embodiment, regions or indicia are preprinted 342 using an ink or other substance which preferably is substantially non-apparent or invisible (such as having a color, reflectivity, texture and the like closely matching that of the unprinted paper), but which, when rubbed or scratched with the edge of a coin, will cause minute amounts of the coin to rub off and adhere only to the printed portion, leaving a visible mark (indicated in Fig. 3 by phantom lines 342). In one embodiment, such indicia are provided by printing using an ink which includes titanium oxide. Thus, it is typically difficult for a would-be
10 counterfeiter to know which indicia should be printed in such non-visible ink since the indicia which are printed in a valid voucher are not readily apparent. However, the voucher may be relatively easily validated using only a ordinarily-available coin, i.e. without the use of special equipment.

Although it is possible to provide perforation of the type described as part of the paper stock 226, in one embodiment, the pattern of perforations is provided in conjunction
15 with the process of printing the value of the voucher using the printer 224. As depicted in Fig. 4, in one embodiment as the paper, following the printing, leaves the printer 224, the paper moves from a first exit position 412 and is conveyed, e.g. by pinch rollers 414a, 414b across the edge of a perforating roller 416 whose edge has, radially protruding therefrom, a plurality of perforation-producing punches or spikes 418. As depicted in Fig.
20 4, the punches 418 are positioned on the edge of the roller 416 in a manner to produce the desired perforation pattern (in the depicted embodiment, in a sinusoidal or wave-like pattern corresponding to the pattern depicted in Figs. 3A and 3B). The paper 412 is thus continuously perforated along its edge as it is conveyed toward a downstream position 422 and, eventually, dispensed to the user. In order to provide the proper rate of rotation 424 of the roller 416 as the paper is moved 426, the rate of rotation 424 of the roller 416 can be controlled and coordinated with the rate of paper movement 426 by a gear train, one or more motor controllers or other coordinator 228 in a manner that will be well known to those of skill in the art after understanding the present disclosure. The roller
25 416 can also be freewheeling, with rotation being driven by the paper movement. Although the perforation is described as occurring upon exit of the paper from the printer,

30

the perforating wheel could also be positioned to provide perforation to the paper as it enters the printer or at other locations that will be apparent to those of skill in the art upon understanding the present disclosure.

In one embodiment, some or all of a unit of the paper supply 226 (such as each roll of thermal paper) is associated with one or more serial numbers or other identifying numbers. In the embodiment of Fig. 5, the paper is preprinted, along the edge of the front surface, with such serial number or serial numbers. In the depicted embodiment, a single serial number is associated with a roll of thermal paper and this number is printed at spaced intervals in a vertical fashion near an edge of the voucher, preferably within less than $\frac{1}{4}$ inch of the edge (similar to the manner described above in connection with the back surface edge printing 316 depicted in connection with Fig. 3B). In order to provide for ease of verifying the validity of the serial number, by the voucher redeemer, the serial number (or serial numbers) associated with the paper supply is also printed by the coin discriminator printer 18, e.g. substantially at the time the voucher value 514 is printed.

In one embodiment, when service personnel load a roll of paper into the paper supply unit 226, such personnel also enter the serial number associated with the roll into the computer 46, e.g. using an I-O device such as a keyboard, touch screen, or similar device 232. In this way, the computer 46 has the information needed to control the printer 18 so as to print an identifier number 516 on the face of the voucher which will match the preprinted serial numbers 512 on the paper stock to permit the grocery store clerk or other redeemer to easily visually verify a match between the preprinted serial number 512 and the discriminator-printed serial number 516.

Although Fig. 5 depicts an embodiment in which a single serial number is associated with a unit of paper stock and is identically printed at intervals 512a, 512b, 512c, it is also possible to provide for identifying numbers which are preprinted on the paper stock, but which change along the length of a voucher or from one voucher to the next, such as incrementing by one or by some other number, or so as to change in some other manner (e.g. which is likely to be substantially unpredictable by a would-be counterfeiter). In this embodiment, it will be necessary for the computer 46 to be able to calculate or detect which preprinted serial number will be positioned near the area where the discriminator-printed number 516 will be printed so that the computer 46 can control

the printer 18 to print a number 516 which will match the closest (or next preceding or succeeding) pre-printed serial number 512b. For example, the printer 18 may be configured to inform the computer 46 of the number of inches of thermal paper that has been thus-far dispensed from the roll. If it is known how the preprinted numbers 512
5 change along the length of the roll (such as incrementing by one for every inch of thermal paper dispensed) the computer 46 will have sufficient information to calculate, in a manner which will be well known to those of skill in the art after understanding the present disclosure, what number to print, using the printer 18, so as to match the closest or next succeeding or preceding preprinted number.

10 In light of the above description, a number of advantages of the present invention can be seen. The present invention provides devices and procedures which facilitate reducing, eliminating, deterring and/or detecting attempts at unauthorized duplication and/or counterfeiting of vouchers. The present invention provides counterfeiting detection features which can be relatively readily implemented such as requiring little or
15 no hardware and/or software modification, and, in some embodiments, requiring only the use of paper or paper stock having one or more of the features as described herein, and, in this manner, at least some features of the present invention can be retrofit, i.e. implemented readily in existing coin discriminators. The present invention provides at least some anti-counterfeiting or counterfeit detection features which use only, or
20 primarily, visual inspection of the voucher and thus at least some features can be implemented without the need for modifying or adding hardware. At least some anti-counterfeiting or counterfeiting detection features can be performed relatively rapidly, such as verifying the correct color of various printing or indicia, correct positioning or registration, correct patterning or configuration of perforations and the like), preferably
25 without requiring the redeemer to flip or rotate the voucher or otherwise manipulate the voucher, or enter data or otherwise handle the voucher (other than, e.g. to hold it up to ordinary light) such that at least some anti-counterfeiting or counterfeit detection features of the present invention can be implemented without substantial delay at a checkout lane. In some embodiments, certain features of the invention are not readily apparent upon
30 visual inspection of a valid voucher and thus would-be counterfeiters may find it difficult to reproduce such features. For example, in one embodiment, at least some indicia are

provided which fluoresce or have other visible characteristics only when exposed to ultraviolet or other special light. According to one embodiment, at least some indicia are provided which are substantially invisible until rubbed or scraped with a coin or similar object. Preferably in some embodiments the voucher is provided with features which are not readily reproduced or counterfeited without using devices or procedures which are typically not available to the general public. For example, perforations which are patterned in a curved, preferably tightly radiused pattern which preferably provides a periodic, smooth and/or repeating pattern and preferably is made using relatively small perforations are typically difficult to provide without special, not-readily-available, equipment.

A number of variations and modifications of the invention can also be used. It is possible to use some features of the invention without using others. For example, it is possible to use non-photocopying inks without using micro perforations, or it is possible to use front/back registered marks without using close-to-the-edge printing. Although the present invention has been described in connection with avoiding, preventing or detecting unauthorized duplication or counterfeiting of a coin-discriminator voucher, the present invention can also be used in connection with avoiding unauthorized duplication or counterfeiting of other items such as coupons, checks, tickets (such as airline, subway or other transportation tickets, game, performance, concert or other event tickets, and the like) negotiable instruments and the like. Although some features of the invention have been described as capable of implementation using a computer, it is possible to use other devices in place of a computer such as one or more application specific integrated circuits (ASIC's) hardwired and/or discrete circuitry, and the like. Although embodiments relating to paper stock serial numbers were described as involving manual entry of serial numbers into the computer, it is also possible to provide for serial number entry by partially or fully automatic scanning or detection, such as using bar code scanners, magnetic ink detectors and the like. Although it is believed many other coin discriminators may involve the use of thermal printers, the present invention can be used in connection with many types of printers including laser printers, inkjet printers, dot matrix printers, line (impact) printers and the like. Although front/back surface registration of a pair of logos and a box was depicted, many shapes or symbols can be used for verifying registration. Although

embodiments have been described which involve pre-printing or pre-providing certain items, it is also possible to use one or more printers housed in the coin discriminator device to print anti-counterfeiting items, such as printing in a fashion and/or with an ink which produces an altered appearance in a photocopy made therefrom.

5 The present invention, in various embodiments, includes components, methods, processes, systems and/or apparatus substantially as depicted and described herein, including various embodiments, subcombinations, and subsets thereof. Those of skill in the art will understand how to make and use the present invention after understanding the present disclosure. The present invention, in various embodiments, includes providing
10 devices and processes in the absence of items not depicted and/or described herein or in various embodiments hereof, including in the absence of such items as may have been used in previous devices or processes, e.g. for improving performance, achieving ease and/or reducing cost of implementation.

 The foregoing discussion of the invention has been presented for purposes of
15 illustration and description. The foregoing is not intended to limit the invention to the form or forms disclosed herein. Although the description of the invention has included description of one or more embodiments and certain variations and modifications, other variations and modifications are within the scope of the invention, e.g. as may be within the skill and knowledge of those in the art, after understanding the present disclosure. It
20 is intended to obtain rights which include alternative embodiments to the extent permitted, including alternate, interchangeable and/or equivalent structures, functions, ranges or steps to those claimed, whether or not such alternate, interchangeable and/or equivalent structures, functions, ranges or steps are disclosed herein, and without intending to publicly dedicate any patentable subject matter.

WHAT IS CLAIMED IS:

1. A method for providing a voucher in a coin discriminator, having a discriminator printer, with the voucher configured to assist in distinguishing unauthorized duplicate or counterfeit vouchers, the method comprising the steps of:

5 providing a computer coupled to said printer and an i/O device coupled to said computer;

printing at least first language on a thermal paper substrate, oriented in a first direction, using a fluorescent ink such that said first language has a first appearance on said thermal paper substrate but wherein a photocopy of first language has a second appearance, different from said first appearance;

10

printing at least second language oriented in a directions about 90 degrees to said first direction positioned less than 0.25 inches from an edge of said thermal paper substrate;

placing a substantially non-visible mark on said thermal paper substrate using a first marking medium;

15

wherein said thermal paper substrate has marked thereon, at least an initial serial number identifying a unit of said thermal paper substrate;

loading said unit of said thermal paper substrate into a position from which thermal paper substrate in said unit can be fed to said discriminator printer;

20 inputting said serial number into said computer using said i/O device;

using said discriminator printer to print, on said thermal paper substrate, at least first indicia containing an indication of a value of said voucher;

printing a number related to said serial number on said thermal paper substrate;

providing a plurality of perforations in said medium to define a first curved pattern of microperforations which includes a region defining a radius of curvature less than about 0.5 inches; and

25

rubbing said non-visible mark with a coin wherein portions of said coin adhere to said non-visible mark to render said mark visible.

2. A method for providing a voucher in a coin discriminator, having a discriminator printer, with the voucher configured to assist in distinguishing unauthorized duplicate or counterfeit vouchers, the method comprising the steps of:

5 placing visible marks on a first substrate using a marking medium which has a first appearance on said substrate but wherein a photocopy of said visible marks has a second appearance, different from said first appearance; and

using said discriminator printer to print, on said substrate, at least first indicia containing an indication of a value of said voucher.

3. A method as claimed in claim 2 wherein said substrate is paper.

10 4. A method as claimed in claim 2 wherein said substrate is thermal paper.

5. A method as claimed in claim 2 wherein said marking medium is fluorescent ink.

15 6. A method for providing a voucher in a coin discriminator, having a discriminator printer, with the voucher configured to assist in distinguishing unauthorized duplicate or counterfeit vouchers, the method comprising the steps of:

placing visible marks on a first substrate using a fluorescent marking medium; and

using said discriminator printer to print, on said substrate, at least first indicia containing an indication of a value of said voucher.

20 7. A method for providing a voucher in a coin discriminator, having a discriminator printer, with the voucher configured to assist in distinguishing unauthorized duplicate or counterfeit vouchers, the method comprising the steps of:

placing visible marks on a first substrate positioned less than 0.25 inches from an edge of said medium; and

25 using said discriminator printer to print, on said substrate, at least first indicia containing an indication of a value of said voucher.

8. A method for providing a voucher in a coin discriminator, having a discriminator printer, with the voucher configured to assist in distinguishing unauthorized duplicate or counterfeit vouchers, the method comprising the steps of:

printing at least first language on said substrate, oriented in a first direction and second language oriented in a direction at a first angle to said first direction; and

using said discriminator printer to print, on said substrate, at least first indicia containing an indication of a value of said voucher.

5 9. A method as claimed in claim 8 wherein said angle is about 90 degrees.

10 10. A method for providing a voucher in a coin discriminator, having a discriminator printer, with the voucher configured to assist in distinguishing unauthorized duplicate or counterfeit vouchers, the method comprising the steps of:

10 using said discriminator printer to print, on a substrate, at least first indicia containing an indication of a value of said voucher; and

providing a plurality of perforations in said substrate to define a first curved pattern of perforations.

15 11. A method as claimed in claim 10 wherein said first curved pattern includes a region defining a radius of curvature less than about 0.5 inches.

15 12. A method as claimed in claim 10 wherein said perforations are microperforations.

13. A method for providing a voucher in a coin discriminator, having a discriminator printer, with the voucher configured to assist in distinguishing unauthorized duplicate or counterfeit vouchers, the method comprising the steps of:

20 placing a substantially non-visible mark on a first substrate using a first marking medium;

using said discriminator printer to print, on said substrate, at least first indicia containing an indication of a value of said voucher; and

25 rubbing said non-visible mark with a coin wherein portions of said coin adhere to said non-visible mark to render said mark visible.

14. A method as claimed in claim 13 wherein said first marking medium comprises white ink containing titanium oxide.

15. A method for providing a voucher in a coin discriminator, having a discriminator printer, with the voucher configured to assist in distinguishing unauthorized duplicate or counterfeit vouchers, the method comprising the steps of:

placing a series of identifier symbols on a first substrate, said series of identifier symbols being spaced from one another; and

using said discriminator printer to print, on said substrate, at least first indicia containing an indication of said identifier.

16. A method as claimed in claim 15 wherein said identifier symbols include a serial number identifying a unit of said substrate.

17. A method as claimed in claim 16 further comprising providing a computer coupled to said printer and an i/O device coupled to said computer and inputting said serial number into said computer using said i/O device.

18. A method as claimed in claim 15 wherein at least some of said series of identifier symbols are different from one another.

19. A method as claimed in claim 18 wherein said series of identifier symbols include a series of numbers which increment by a predetermined amount.

20. A voucher for dispensing from a coin discriminator comprising:

a thermal paper substrate;

at least a first fluorescent ink region printed on a surface of said substrate; and

a plurality of microperforations through said substrate defining at least a first curved pattern.

21. Apparatus for use in outputting results from a coin discriminator having a discriminator printer, with the voucher configured to assist in distinguishing unauthorized duplicate or counterfeit vouchers, comprising:

a computer coupled to said printer;

a thermal paper substrate having

at least first language printed on said substrate, oriented in a first direction, using a fluorescent ink such that said first language has a first

appearance on said thermal paper substrate but wherein a photocopy of first language has a second appearance, different from said first appearance;

5 at least second language printed on said substrate oriented in a direction about 90 degrees to said first direction positioned less than 0.25 inches from an edge of said thermal paper substrate;

 a substantially non-visible mark on said thermal paper substrate wherein when said non-visible mark is rubbed with a coin, portions of said coin adhere to said non-visible mark to render said mark visible;

10 wherein said thermal paper substrate has marked thereon, at least an initial serial number identifying a unit of said thermal paper substrate;

 said thermal paper substrate located in a position from which thermal paper substrate can be fed to said discriminator printer;

 i/O means for inputting said serial number into said computer;

15 means for controlling said discriminator printer to print, on said thermal paper substrate, at least first indicia containing an indication of a value of said voucher;

 means for controlling said discriminator printer to print a number related to said serial number on said thermal paper substrate; and

20 a plurality of perforations in said medium defining a first curved pattern of microperforations which includes a region defining a radius of curvature less than about 0.5 inches.

22. A method for providing a secure voucher substantially as described and depicted herein.

23. A secure voucher substantially as described and depicted herein.

25 24. A coin discriminator substantially as described and depicted herein.

1/4




FIG. 1